and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.

SIGNAL NAME	FROM PIN	TO PIN	COLOR	REMARKS
+5V	B03D2	H02A2	RED	
+5V	B03E2	H03A2		
+5V	B03F2	J02A2		
+5V	B03H2	J03A2	RED	
-15V	B03L2	A02B2	BLUE	
-15V	B03M2	A03B2		
-15V	B03N2	B02B2		
-15V	B03P2	B03B2		
-15V	B03R2	H02B2		
-15V	B03S2	H03B2		
-15V	B03T2	J02B2		
-15V	B03U2	J03B2	BLUE	
GND	A02T1	A03U1	BLK	
GND	A03U1	A03V1		
GND	A03V1	A04T1		
GND	B02T1	B03U1		
GND	B03U1	B03V1		
GND	B03V1	B04T1	BLK	
	BØ3K2	CØ2B2	BLUE	

*NOTE: ALL WIRES TO BE INSTALLED WITH 24 GAUGE A.W.G. +5 IN RED, -15 IN BLUE, AND GND. IN BLACK. A SPECIAL CHUCK TO BE USED FOR #24 WIRE AND 30 GAUGE PINS.

REVISIONS			
REV.	DATE	CHG. NO.	APP'D.

DRN	I.T.	DATE 1/68
CHK'D.		DATE
ENG.		DATE
PROJ. ENG.		DATE
PROD.		DATE
FIRST USED ON		
SCALE		
SHEET 2 OF 2		

digital EQUIPMENT CORPORATION
MAYNARD, MASSACHUSETTS

TITLE
GENERAL WIRING SHEET
FOR POWER WIRES

SIZE	CODE	NUMBER	REV.
A	WL	BI-0-26	A

DIST.

DEC FORM NO.