



UNLESS OTHERWISE INDICATED:
 RESISTORS ARE 1/4W, 10%
 CAPACITORS ARE MMFD
 R8, R9 & R19 ARE 1/4W; 0.01%; 5ppm

USE THE ETCHED BOARD OF THE A602

| TRANSISTOR & DIODE CONVERSION CHART | | | |
|-------------------------------------|------------|-----|-----|
| DIC | EIA | DIC | EIA |
| DEC2894-3 | 17C-2894-3 | | |
| DEC3009 | 2N1305W | | |
| 2N1305W | NONE | | |
| D-662 | 1N645 | | |
| D-007 | 1N277 | | |

NOTES

THIS SCHEMATIC IS FURNISHED ONLY FOR TEST AND MAINTENANCE PURPOSES. THE CIRCUITS ARE PROPRIETARY IN NATURE AND SHOULD BE TREATED ACCORDINGLY.

COPYRIGHT 1964 BY DIGITAL EQUIPMENT CORPORATION

| | | |
|--|-----------|---|
| 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 | | |
| B | R5-B-A603 | 1 |
| 2 BIT DAC A603 | | |