

IDENTIFICATION

PRODUCT CODE: MAINDEC-08-DHTMA-A-D
PRODUCT NAME: TMB-E CONTROL TEST PART 1
DATE CREATED: DECEMBER 4, 1972
MAINTAINER: DIAGNOSTIC GROUP
AUTHOR: LEONARD E. BEYERSDORFER

COPYRIGHT (C) 1972
DIGITAL EQUIPMENT CORPORATION
MAYNARD, MASS. 01754



NOTE

THERE ARE SIX DIAGNOSTIC PROGRAMS ASSOCIATED WITH THE TM8-E DECMAGTAPE CONTROL AND ITS TRANSPORT SYSTEM. ALTHOUGH PHYSICALLY SEPARATE, THESE PROGRAMS MUST BE TREATED AS A LARGE INTEGRATED TEST, AND TO ENSURE PROPER SYSTEM OPERATION, THESE TESTS MUST BE EXECUTED IN THE ORDER DELINEATED BELOW.

IF A GIVEN TEST SHOULD FAIL AND IT APPEARS THAT A FIX HAS BEEN FOUND, ALL PROGRAMS MUST ONCE AGAIN BE RUN, ONLY WHEN ALL TESTS HAVE RUN WITHOUT ANY UNACCEPTABLE ERRORS CAN THE TM8-E SYSTEM BE CONSIDERED UP.

TM8-E DIAGNOSTIC PROGRAMS' ORDER OF EXECUTION

1. TM8-E CONTROL TEST PART 1 (MAINDEC-08-DHTMA)
2. TM8-E CONTROL TEST PART 2 (MAINDEC-08-DHTM8)
3. TM8-E DRIVE FUNCTION TIMER (MAINDEC-08-DHTMC)
4. TM8-E DATA RELIABILITY 9 TRACK (MAINDEC-08-DHTMD)
5. TM8-E DATA RELIABILITY 7 TRACK (MAINDEC-08-DHYME)
6. TM8-E RANDOM EXERCISER (MAINDEC-08-DHTMF)

TABLE OF CONTENTS

1.	ABSTRACT
2.	REQUIREMENTS
2.1	HARDWARE
2.2	MEMORY
2.3	PRELIMINARY PROGRAMS
3.	CONVENTIONS
4.	PROGRAM LOADING PROCEDURE
5.	PROGRAM STARTING PROCEDURE
6.	STANDARD TEST PROCEDURE
7.	PROGRAM CONTROLS
7.1	PROGRAM MONITOR CONTROL VIA KEYBOARD COMMANDS
8.1.1	TEST SELECTION COMMANDS
7.1.2	TEST CONTINUATION COMMANDS
7.1.3	TEST INTERRUPT COMMAND
7.1.4	MISCELLANEOUS COMMANDS
7.2	SWITCH REGISTER CONTROL OPTIONS
8.	ERRORS
8.1	ERROR HALTS
8.2	ERROR REPORTS
8.3	STANDARD ERROR RECOVERY PROCEDURE
8.3.1	SUBTEST LOOPS
9.	RESTRICTIONS
10.	EXECUTION TIME
11.	TEST ABSTRACTS
12.	LISTING

1. ABSTRACT

THE TM8-E CONTROL TEST PART 1 IS AN INTEGRATED SERIES OF SUB-TESTS DESIGNED TO AID IN THE CHECKOUT AND MAINTENANCE OF THE TM8-E DECMAGTAPE CONTROL WITHOUT DEPENDENCE ON TRANSPORT SYSTEM USE. VERSATILITY OF USAGE IS AFFORDED THROUGH A MODEST KEYBOARD MONITOR AND SWITCH REGISTER CONTROL OPTIONS.

THIS PROGRAM CONSISTS OF 12 MAJOR TESTS (TEST 01 THROUGH TEST 14) EACH OF WHICH CONSISTS OF A NUMBER OF SUBTESTS DESIGNATED BY THE LETTERS A THROUGH Z.

2. REQUIREMENTS

2.1 HARDWARE

PDP-8/E, 8/M, 8/F
TELETYPE OR COMPATIBLE DEVICE (TTY)
TM8-E DECMAGTAPE CONTROL

2.2 MEMORY

THIS PROGRAM REQUIRES 4K OF MEMORY AND MAY RESIDE IN ANY MEMORY FIELD; ALL OF EXISTING MEMORY IS USED TO TEST THE ABILITY OF THE TM8-E TO ADDRESS CORRECTLY DURING DMA TRANSFERS.

2.3 PRELIMINARY PROGRAMS

ALL PROCESSOR/MEMORY DIAGNOSTICS